

VIMEK 610 SE

VIMEK®



New powerful Common Rail engine

at 68 Hp Stage 3B/4 Final

Crane with extension arm as option

Crane reach total 6,50 m

New powerful hydrostatic

Drive modes "Forest", "Road" and "ECO"

New load sensitive hydraulic system

Improved crane manoeuvring

Vimek Tilt grapple generation 2 as option

offers unique characteristics

VIMEK 610 SE

TECHNICAL SPECIFICATION

Motor

CAT C2,2T CRDI 50 kW

Transmission

Hydrostatic / mechanical

Front tires

500/60-22,5 or 405/70-24

Rear tires

400/60-15,5

Ground clearness

40 cm

Hydraulic

Flow 85 l/min 175 bar

Length

Standard 6,90 m (load length 3,30 m, loading area 1,85 m²)

Short 6,70 m (load length 3,00 m, loading area 1,85 m²)

Long 7,60 m (load length 4,00 m, loading area 1,65 m²)

Width

1,90 m or 2,00 m

Loading capacity

5,000 kg

Weight incl. crane

4,700 Kg

Crane

Vimek - Mowi P25

– Max reach, 5,20 m

– Lifting capacity at 5,20 m, 400 kg

– Gripping area, 0,16 m²

EQUIPMENT

Standard

Air condition

Half LED lights including roof frame

Radio with Bluetooth

Options

Telescopic crane

Tilt grapple 0,16 m²

Crane damping system

Pneumatic chair

Refueling pump for hydraulic oil

Refueling pump for diesel

Radio controlled hydraulic winch

Sun blinds

Diesel engine heating system

Callstart for diesel engine

Full LED lights including roof frame

Sprinkler system

PC with rear camera

Rear camera

Tow hitch

Extra accessories

Wheel tracks

Wheel chains 500/60-22,5 or 405/70-24

Bucket attachment

Dolly trailer

Chain saw holder

*The machine on the picture can be extra equipped.

© 2013 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, their respective logos, Caterpillar Yellow, the "Power Edge" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and Aug not be used without permission.

Version 1, June 2017

VIMEK®

For more information and to find your nearest retailer, please visit our website
www.vimek.com