

VIMEK 606 TTW

VIMEK®



Loading capacity of 3000 kg

more than its own weight

Wider cabin

improved driver environment

Low impact forwarder

Transport with Dolly

for cost effective transportation

VIMEK 606 TTW

TECHNICAL SPECIFICATION

Engine

Kubota D 902-E, 18 kW/3600 rpm

Transmission

Variable mechanical

Front tyres

405/70-24

Rear tyres

400/60-15,5

Ground clearness

40 cm

Hydraulic

Flow 43 l/min 175 bar

Length

Standard: 6,20 m (load length 3,20 m load area 1,40m²)

Long: 6,70 m (load length 3,70 load area 1,40 m²)

Width

1,80 m

Loading capacity

3000 kg

Weight

2 960 kg

Crane

Vimek - Mowi 2046

– Max reach, 4,60 m

– Lifting capacity 4,60 m 375 kg

– Gripping area, 0,16 m²

EQUIPMENT

Options

Air condition

Radio controlled hydraulic winch

Crane damping system

Radio with Bluetooth

LED lights

Sun blinds

Diesel engine heating system

Callstart for diesel engine

220 volt engine heating system

Pneumatic chair

Extra accessories

Bogie tracks

Wheel chains

Bucket attachment

Chain saw holder

VIMEK®

For more information and to find your nearest retailer, please visit our website
www.vimek.com

*The machine on the picture can be extra equipped.

Version 1, June 2017